



ACERINOX EUROPA FABRICA DEL CAMPO DE GIBRALTAR PALMONES (LOS BARRIOS) T.FNO. (34) - 956 62 93 00 FAX (34) - 956 62 93 11 P.O. BOX 83 11370 LOS BARRIOS (CADIZ) ESPAÑA	 by Accredited Body	INSPECTION CERTIFICATE CERTIFICADO DE INSPECCION 3.1																		
CUSTOMER CLIENTE OIKI ACCIAI INOSSIDABILI SPA VIA PARADIGNA, 95/A 43100 PARMA ITALIA		OUR ORDER N° N° PEDIDO SO 93425		YOUR ORDER N° S° PEDIDO BO-194		CERTIFICATE N° CERTIFICADO N° F0 2020 23394 20002 *														
REQUIREMENTS NORMAS APLICABLES EN 10028-7/TRD 100/AD-2000-MERKBLATT W0/W2/W10 PED2014/68/EU EN 10088-2:2014 ASTM A240Ed19/A480Ed19-ASME SecIIA SA240/SA480Ed19 EN 10088-2:2014 ASTM A240Ed19/A480Ed19-ASME SecIIA SA240/SA480Ed19		INTERGRANULAR CORROSION CORROSIÓN INTERGRANULAR EN ISO 3651-2 EN ISO 3651-2 ASTM-A-262 PRACTICA E EN ISO 3651-2 ASTM-A-262 PRACTICA E		INSPECTOR'S STAMP SELLO DEL INSPECTOR 4511		STEELMAKING PROCESS PROCESO DE ACERÍA A.O.D.														
COIL / BOX BOBINA / CAJA 04Z6TP A 04Z6TP B	CONTENT CONTENIDO 04Z6TP A 04Z6TP B	DIMENSIONS (mm) DIMENSIONES <table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>THICKNESS</th> <th>WIDTH</th> <th>LENGTH</th> </tr> <tr> <td>ESPESOR</td> <td>ANCHO</td> <td>LARGO</td> </tr> <tr> <td>3,000</td> <td>1500,00</td> <td></td> </tr> <tr> <td>3,000</td> <td>1500,00</td> <td></td> </tr> </table>		THICKNESS	WIDTH	LENGTH	ESPESOR	ANCHO	LARGO	3,000	1500,00		3,000	1500,00		MARKS MARCA 4 5	QUANTITY CANTIDAD 1 1	TEST N° PROBETA 04Z6TP 04Z6TP		
THICKNESS	WIDTH	LENGTH																		
ESPESOR	ANCHO	LARGO																		
3,000	1500,00																			
3,000	1500,00																			
CHEMICAL ANALYSIS / COMPOSICIÓN QUÍMICA (%)																				
HEAT N° COLADA Z6TP	C	CR	MN	N	NI	P	S	SI	CO	CU										
	0,020	18,180	1,845	0,092	8,015	0,032	0,001	0,362	0,230	0,490										
MECHANICAL PROPERTIES / CARACTERÍSTICAS MECÁNICAS																				
TEST N° PROBETA 04Z6TP	PROBE SIT TYPE C T	Rm N/mm2 632,16	Rp 0.2 N/mm2 320,24	Rp 1.0 N/mm2 355,65	A50 % 54,59	A5 % 56,59	HRB 84,00													
REMARKS / OBSERVACIONES Spectrochemical identity test O.K. Heat treatment: 1050-1100°C. Cooling with air. Issued in agreement with TÜV SÜD Industrie Service GmbH (02/1983). The delivery is in accordance with the order Temperatura de hipertemple entre 1050 y 1100 ° C. NACE-MR0175/ISO 15156-3:2009;NACE MR0103:2012/ISO 17945:2015 (Chem & Mech only) MATERIAL FREE OF RADIOACTIVITY									SURFACE AND DIMENSIONAL CONTROL INSPECCIÓN SUPERFICIAL Y DIMENSIONAL SATISFACTORY SATISFACTORIA											
WORK INSPECTOR INSPECTOR  A. Heredia									Palmones, 26 Agosto 2020											

ACERINOX EUROPA FABRICA DEL CAMPO DE GIBRALTAR PALMONES (LOS BARRIOS) TFM. (34) - 956 62 93 00 FAX (34) - 956 62 93 11 P.O. BOX 83 11370 LOS BARRIOS (CADIZ) ESPAÑA	 by Accredited Body	 0769-CPR-VAS-00530 DoP no. 1/2015	INSPECTION CERTIFICATE CERTIFICADO DE INSPECCION 3.1																																																							
CUSTOMER CLIENTE OIKI ACCIAI INOSSIDABILI SPA VIA PARADIGNA, 95/A 43100 PARMA ITALIA			OUR ORDER N° N° PEDIDO SO 93425	YOUR ORDER N° S° PEDIDO BO-194																																																						
REQUIREMENTS NORMAS APLICABLES EN 10088-4:2009			INTERGRANULAR CORROSION CORROSIÓN INTERGRANULAR	STEELMAKING PROCESS PROCESO DE ACERÍA A.O.D.																																																						
COIL / BOX BOBINA / CAJA 04Z6TP A 04Z6TP B			CONTENT CONTENIDO 04Z6TP A 04Z6TP B	DIMENSIONS (mm) <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>THICKNESS</th> <th>WIDTH</th> <th>LENGTH</th> </tr> <tr> <th>ESPEZOR</th> <th>ANCHO</th> <th>LARGO</th> </tr> </thead> <tbody> <tr> <td>3,000</td> <td>1500,00</td> <td></td> </tr> <tr> <td>3,000</td> <td>1500,00</td> <td></td> </tr> </tbody> </table>	THICKNESS	WIDTH	LENGTH	ESPEZOR	ANCHO	LARGO	3,000	1500,00		3,000	1500,00																																											
THICKNESS	WIDTH	LENGTH																																																								
ESPEZOR	ANCHO	LARGO																																																								
3,000	1500,00																																																									
3,000	1500,00																																																									
CHEMICAL ANALYSIS / COMPOSICIÓN QUÍMICA (%)			MARKS MARCA 4 5	QUANTITY CANTIDAD 1 1																																																						
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>HEAT N°</th> <th>C</th> <th>CR</th> <th>MN</th> <th>N</th> <th>NI</th> <th>P</th> <th>S</th> <th>SI</th> <th>CO</th> <th>CU</th> </tr> <tr> <th>COLADA</th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>REQUIREMENTS</td> <td></td> <td>17,500</td> <td></td> <td></td> <td>8,000</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>REQUISITOS</td> <td>0,030</td> <td>19,500</td> <td>2,000</td> <td>0,100</td> <td>10,500</td> <td>0,045</td> <td>0,015</td> <td>1,000</td> <td></td> <td></td> </tr> <tr> <td>Z6TP</td> <td>0,020</td> <td>18,180</td> <td>1,845</td> <td>0,092</td> <td>8,015</td> <td>0,032</td> <td>0,001</td> <td>0,362</td> <td>0,230</td> <td>0,490</td> </tr> </tbody> </table>			HEAT N°	C	CR	MN	N	NI	P	S	SI	CO	CU	COLADA											REQUIREMENTS		17,500			8,000						REQUISITOS	0,030	19,500	2,000	0,100	10,500	0,045	0,015	1,000			Z6TP	0,020	18,180	1,845	0,092	8,015	0,032	0,001	0,362	0,230	0,490	TEST N° PROBETA 04Z6TP 04Z6TP
HEAT N°	C	CR	MN	N	NI	P	S	SI	CO	CU																																																
COLADA																																																										
REQUIREMENTS		17,500			8,000																																																					
REQUISITOS	0,030	19,500	2,000	0,100	10,500	0,045	0,015	1,000																																																		
Z6TP	0,020	18,180	1,845	0,092	8,015	0,032	0,001	0,362	0,230	0,490																																																
MECHANICAL PROPERTIES / CARACTERÍSTICAS MECÁNICAS			<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>TEST N°</th> <th>Rm</th> <th>Rp 0.2</th> <th>Rp 1.0</th> <th>A5</th> <th>HRB</th> </tr> <tr> <th>PROBETA</th> <th>N/mm2</th> <th>N/mm2</th> <th>N/mm2</th> <th>%</th> <th></th> </tr> </thead> <tbody> <tr> <td>REQUIREMENTS</td> <td>520,00</td> <td>220,00</td> <td>250,00</td> <td>45,00</td> <td></td> </tr> <tr> <td>REQUISITOS</td> <td>700,00</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>04Z6TP</td> <td>632,16</td> <td>320,24</td> <td>355,65</td> <td>56,59</td> <td>84,00</td> </tr> </tbody> </table>		TEST N°	Rm	Rp 0.2	Rp 1.0	A5	HRB	PROBETA	N/mm2	N/mm2	N/mm2	%		REQUIREMENTS	520,00	220,00	250,00	45,00		REQUISITOS	700,00					04Z6TP	632,16	320,24	355,65	56,59	84,00																								
TEST N°	Rm	Rp 0.2	Rp 1.0	A5	HRB																																																					
PROBETA	N/mm2	N/mm2	N/mm2	%																																																						
REQUIREMENTS	520,00	220,00	250,00	45,00																																																						
REQUISITOS	700,00																																																									
04Z6TP	632,16	320,24	355,65	56,59	84,00																																																					
REMARKS / OBSERVACIONES The delivery is in accordance with the order MATERIAL FREE OF RADIOACTIVITY			SURFACE AND DIMENSIONAL CONTROL INSPECCIÓN SUPERFICIAL Y DIMENSIONAL SATISFACTORY SATISFACTORIA																																																							
			WORK INSPECTOR INSPECTOR  A. Heredia																																																							
			Palmones, 26 Agosto 2020																																																							